# NSN 5935-01-273-6708

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-273-6708

**Body Style:** 

Right angle type

**Overall Length:** 

Between 1.526 inches and 1.556 inches

**Overall Width:** 

Between 0.644 inches and 0.683 inches

**Body Height:** 

Between 0.479 inches and 0.509 inches

**Environmental Protection:** 

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:** 

Between 1.307 inches and 1.317 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

15 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, gr c, cl 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Pin single mating end single contact grouping

**Shell Material:** 

Metal

**Shell Surface Treatment:** 

Cadmium and chromate

# NSN 5935-01-273-6708

Electrical Receptacle Connector - Page 2 of 2



## **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification all treatment responses

## **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end or mil-m-24519, ty gpt-30f or ty get-30f military specification single material response single mating end

## **Included Contact Quantity:**

15 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.015 gold grains, troy

## **Precious Material:**

Gold

## **Test Data Document:**

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-c-24308/24 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.