## NSN 5935-01-273-7280

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-273-7280 **Thread Class:** 2a **Body Style:** Straight shape, external coupling **Overall Length:** 0.885 inches **Overall Height:** 1.688 inches **Overall Width:** 1.688 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.375 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** 1.375 inches **Distance From Mounting Shoulder To Front Face:** 0.322 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 24-61 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 126.0 Shell Type: Solid Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.438 inches **Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

## NSN 5935-01-273-7280

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Glass fiber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel and cadmium
Included Contact Quantity:
61 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0