Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-273-7281

Thread Class:
2a
Body Style:
Straight shape, external coupling
Overall Length:
0.885 inches
Overall Height:
0.812 inches
Overall Width:
0.812 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.594 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.594 inches
Distance From Mounting Shoulder To Front Face:
0.322 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
8-dec single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
85.0
Shell Type:
Solid
Thready Qty Per Inch (tpi):
28 Thread Circle
Thread Size:
0.438 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping



## **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Glass fiber single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Nickel and cadmium **Included Contact Quantity:** 8 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: Demilitarization:

No

---

Fiig:

A039b0