# NSN 5935-01-273-7894

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-273-7894

**Body Style:** 

Right angle type

**Overall Length:** 

Between 6.425 inches and 6.435 inches

**Overall Height:** 

Between 0.920 inches and 0.940 inches

**Overall Width:** 

Between 0.405 inches and 0.455 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.073 inches and 0.077 inches

**Distance Between Mounting Facility Centers:** 

Between 6.195 inches and 6.205 inches

**Mating End Quantity:** 

1

#### **Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

## **Polarization Method:**

Guide pin/socket

Shell Type:

Solid

## **Connector Locking Method:**

Friction

## **Terminal Location:**

Side single mating end single contact grouping

#### **Contact Material:**

Copper alloy 260 single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# **Insert Material:**

Plastic polyamide single mating end

#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, gr c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

#### **Terminal Type:**

Pin single mating end single contact grouping

# **Contact Material Specification:**

Qq-b-613 federal specification single material response single mating end single contact grouping

#### **Guide Design And Location:**

D shape pin right-hand at 11 oclock

# NSN 5935-01-273-7894

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Shell Material Specification:
Qq-a-200/8, t6 federal specification single material response
Insert Material Specification:
Mil-m-20693, type 1 military specification single material response single mating end
Included Contact Quantity:
116 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.116 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.