

View Online at <https://aerobasegroup.com/nsn/5935-01-273-7946>

**Thread Class:**

2b and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling w/backshell

**Overall Length:**

1.000 inches

**Overall Diameter:**

0.800 inches

**Cable Entrance Diameter:**

Between 0.195 inches and 0.216 inches

**Mounting Facility Thickness:**

Between 0.045 inches and 0.240 inches

**Threaded Device Type:**

Coupling facility and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bnc single mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded shell

**Connector Cable Strain Relief Method:**

Crimp type

**Thready Qty Per Inch (tpi):**

28 and 28

**Thread Size:**

0.437 inches and 0.500 inches

**Criticality Code Justification:**

Feat

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver and copper

**Shell Surface Treatment Specification:**

Qq-s-365 federal specification 1st treatment response

**Bushing Accommodation Hole Shape:**

Round w/flat

**Special Features:**

Contact diameter 0.271 in. Min and 0.276 in. Max

**Precious Material And Location:**

Body surface silver

**Precious Material And Weight:**

0.100 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0