

View Online at https://aerobasegroup.com/nsn/5935-01-273-7946

# Thread Class:

2b and 2a

## Thread Direction:

Right-hand and right-hand

## Body Style:

Straight shape, external coupling w/backshell

#### Overall Length:

1.000 inches

**Overall Diameter:** 

0.800 inches

Cable Entrance Diameter:

Between 0.195 inches and 0.216 inches

### **Mounting Facility Thickness:**

Between 0.045 inches and 0.240 inches

#### **Threaded Device Type:**

Coupling facility and mounting bushing

## Mating End Quantity:

1

### **Contact Position Arrangement Style:**

Bnc single mating end

Shell Type:

Solid

### **Connector Locking Method:**

Internally threaded shell

### **Connector Cable Strain Relief Method:**

Crimp type

### Thready Qty Per Inch (tpi):

28 and 28

### Thread Size:

0.437 inches and 0.500 inches

### Criticality Code Justification:

Feat

#### **Shell Material:**

Copper alloy

#### Shell Surface Treatment:

Silver and copper

### Shell Surface Treatment Specification:

Qq-s-365 federal specification 1st treatment response

### **Bushing Accommodation Hole Shape:**

Round w/flat

#### **Special Features:**

Contact diameter 0.271 in. Min and 0.276 in. Max



Precious Material And Location:

Body surface silver

Precious Material And Weight:

0.100 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0