

View Online at <https://aerobasegroup.com/nsn/5935-01-274-1367>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape threaded

**Overall Length:**

1.046 inches

**Overall Diameter:**

1.313 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.130 inches and 0.150 inches

**Mounting Facility Thickness:**

0.063 inches

**Threaded Device Type:**

Coupling facility and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

18-1 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

10.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end 1st contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end 1st contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Length:**

0.625 inches

**Thready Qty Per Inch (tpi):**

18 and 20

**Thread Size:**

1.125 inches and 1.000 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Steel single mating end all contact groupings

**Contact Surface Treatment:**

Tin single mating end all contact groupings and cadmium single mating end all contact groupings and copper single mating end all contact groupings

**Insert Material:**

Glass single mating end

**Contact Surface Treatment Specification:**

Mil-t-10727, type 1 military specification 1st treatment response single mating end all contact groupings and qq-p-416, type 1 federal specification 2nd treatment response single mating end all contact groupings

**Terminal Type:**

Tab, solder lug single mating end all contact groupings

**Shell Material:**

Steel

**Shell Surface Treatment:**

Tin and cadmium and copper

**Shell Surface Treatment Specification:**

Mil-t-10727, type 1 military specification 1st treatment response and qq-p-416, type 1 federal specification 2nd treatment response

**Included Contact Quantity:**

6 single mating end 2nd contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Round pin single mating end all contact groupings

**Thread Series Designator:**

Unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-t-10727 spec.