

View Online at https://aerobasegroup.com/nsn/5935-01-274-1383

| Thread Class: |
|--|
| 2a and 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Hood, top opening w/clamp |
| Overall Length: |
| 1.312 inches |
| Overall Height: |
| 2.406 inches |
| Overall Width: |
| 0.625 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 18 single mating end |
| Polarization Method: |
| Jackscrew |
| Shell Type: |
| Hood, top opening |
| Connector Locking Method: |
| Jackscrew-socket |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Cable Opening Length: |
| 0.609 inches |
| Cable Opening Width: |
| 0.438 inches |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.112 inches |
| Insert Material: |
| Glass fiber and plastic diallyl phthalate single mating end |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Aluminum alloy |
| Insert Material Specification: |
| Mil m 14, ty add f military aposition all material reaponess single mating and |

Mil-m-14, ty sdg-f military specification all material responses single mating end



Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.