Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-274-4092

| Thread Classe |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Rectangular shape center screwlock |
| Overall Length: |
| 2.790 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.470 inches |
| Overall Height: |
| 3.250 inches |
| Overall Width: |
| 0.902 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 132 single mating end |
| Polarization Method: |
| Polarization boss |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Jackscrew |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.138 inches |
| Insert Material: |
| Glass fiber single mating end and plastic diallyl phthalate single mating end |
| Shell Material: |
| Steel comp 302 |
| Shell Surface Treatment: |
| Passivate |
| Shell Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Shell Material Specification: |
| Qq-s-766 federal specification single material response |
| Insert Material Specification: |

Mil-m-14, ty sdg-f military specification all material responses single mating end



Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.