

View Online at <https://aerobasegroup.com/nsn/5935-01-274-6562>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight type

Overall Length:

2.200 inches

Overall Height:

0.689 inches

Overall Width:

Between 0.289 inches and 0.302 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

Distance Between Mounting Facility Centers:

2.050 inches

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end 1st contact grouping

Polarization Method:

Guide pin/socket and contact

Connector Locking Method:

Friction

Thread Length:

0.085 inches

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end and plastic polyester single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, gr c military specification 1st treatment response single mating end 1st contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end 1st contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug single mating end 1st contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end 1st contact grouping or qq-c-533 federal specification single material response single mating end 1st contact grouping or qq-b-750 federal specification single material response single mating end 1st contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification all material responses single mating end

Included Contact Quantity:

35 single mating end 1st contact grouping

Included Contact Type:

Hermaphrodite single mating end 1st contact grouping

Special Features:

Left-hand end guide gold color; right-hand end guide silver color; contact number 2 omitted for polarization

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.035 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-55302/52 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.