NSN 5935-01-274-9110

Electrical Receptacle Connector - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5935-01-274-9110
Body Style:
Straight type
Overall Length:
0.606 inches
Overall Width:
0.240 inches
Body Height:
0.265 inches
Environmental Protection:
Thermal shock resistant and vibration proof and moisture resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Connector Locking Method:
Friction
End Application:
5895-01-205-0662 control eccm module
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type ii military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification
2nd treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-750, composition a federal specification single material response single mating end single contact grouping
Insert Material Specification:

Included Contact Quantity:

10 single mating end single contact grouping

Included Contact Type:

Flat socket single mating end single contact grouping

Mil-m-14 military specification single material response single mating end

NSN 5935-01-274-9110

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.010 gold grains, troy
Precious Material:
Gold
Specification Data:
80063-a3028199 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.