## NSN 5935-01-275-1982

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-275-1982

Body Style:
Straight type
Overall Length:
0.812 inches
Overall Width:
0.400 inches
Body Height:
0.440 inches
Environmental Protection:
Thermal shock resistant and heat resistant and cold resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Latch
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204, class ii military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal
specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-750, composition a federal specification single material response single mating end single contact grouping
Included Contact Quantity:
14 single mating end single contact grouping

## Included Contact Type:

Flat pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

## NSN 5935-01-275-1982

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.014 gold grains, troy
Precious Material:
Gold
Specification Data:
80063-a3024459 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.