

View Online at <https://aerobasegroup.com/nsn/5935-01-275-2974>

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

25.5 millimeters

Overall Diameter:

20.0 millimeters

Environmental Protection:

Thermal shock resistant and salt water resistant

Distance From Mounting Shoulder To Front Face:

16.0 millimeters

Mounting Facility Thickness:

3.0 millimeters

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

7 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

0.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

100.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

90.0 and 120.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

End Application:

5895-01-205-0645 converter

Thread Size:

14.0 millimeters

Thread Pitch In Millimeters:

0.75

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty ii, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Chromium

Shell Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

Thread Tolerance Class:

6g external

Included Contact Quantity:

7 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.007 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Iso m

Specification Data:

80063-a3030414 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.