NSN 5935-01-275-4915

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-275-4915 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 0.850 inches **Overall Height:** 0.605 inches **Overall Width:** 0.250 inches **Environmental Protection:** Heat resistant and cold resistant and vibration resistant and shock resistant and salt water resistant and humidity resistant **Distance Between Mounting Facility Centers:** 0.650 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction Thready Qty Per Inch (tpi): **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:**

Gold single mating end single contact grouping Insert Material:

Plastic polyphenylene single mating end

NSN 5935-01-275-4915

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping and qq-c-533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-24519 military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

10 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Hoods are supplied unassembled

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.