## NSN 5935-01-275-5840

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-275-5840

**Body Style:** 

Right angle type

**Overall Length:** 

1.275 inches

**Overall Width:** 

0.200 inches

**Body Height:** 

Between 0.115 inches and 0.135 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end 1st contact grouping

**Contact Maximum Current Rating In Amps:** 

1.0 single mating end 1st contact grouping

**Polarization Method:** 

Mating end

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Side single mating end 1st contact grouping

**Contact Material:** 

Copper alloy single mating end 1st contact grouping

**Contact Surface Treatment:** 

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping

**Insert Material:** 

Plastic polyethylene single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification 1st treatment response single mating end 1st contact grouping and qq-n-290 federal specification 2nd treatment response single mating end 1st contact grouping

**Criticality Code Justification:** 

Feat

**Terminal Type:** 

Tab, solder lug single mating end 1st contact grouping

**Contact Material Specification:** 

Qq-b-750 federal specification single material response single mating end 1st contact grouping

**Included Contact Quantity:** 

48 single mating end 1st contact grouping

**Included Contact Type:** 

Round socket single mating end 1st contact grouping

**Special Features:** 

Polarizing pin in position 25

## NSN 5935-01-275-5840

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.048 gold grains, troy
Precious Material:
Gold
Specification Data:
73030-791723 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.