

View Online at <https://aerobasegroup.com/nsn/5935-01-275-7270>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape w/screw locks

**Overall Length:**

2.350 inches

**Overall Height:**

0.965 inches

**Overall Width:**

0.250 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Connector Locking Method:**

Jackscrew-socket

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.086 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polyphenylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-24519 military specification single material response single mating end

**Included Contact Quantity:**

40 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Hoods are supplied unassembled

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.040 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.