NSN 5935-01-275-8203

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-275-8203

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Angle shape, external/internal coupling
Overall Length:
1.910 inches
Overall Height:
2.500 inches
Overall Width:
0.690 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
2
Contact Position Arrangement Style:
Tnc all mating ends
Contact Removability:
Removable all mating ends single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring and externally threaded shell
Thready Qty Per Inch (tpi):
28
Thread Size:
0.438 inches
Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Silver all mating ends single contact grouping
Insert Material:
Plastic polytetrafluoroethylene all mating ends
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response all mating ends single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response all mating ends single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Passivate

NSN 5935-01-275-8203

Connector Adapter - Page 2 of 2



Shell Surface Treatment Specification:

Astm a380-78 assn standard single treatment response

Shell Material Specification:

Astm 840 assn standard single material response

Insert Material Specification:

Mil-p-19468 military specification single material response all mating ends

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Coaxial socket 2nd mating end single contact grouping

Special Features:

Body angle 125.0 deg

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.010 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19468 spec.