NSN 5935-01-275-8220

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-275-8220

Body Style: Right angle type **Overall Length:** 0.175 inches Overall Width: 0.200 inches **Body Height:** Between 0.115 inches and 0.135 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end 1st contact grouping **Contact Maximum Current Rating In Amps:** 1.0 single mating end 1st contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction **Terminal Location:** Side single mating end 1st contact grouping **Contact Material:** Copper alloy single mating end 1st contact grouping **Contact Surface Treatment:** Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping **Insert Material:** Plastic polyethylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response single mating end 1st contact grouping and qq-n-290 federal specification 2nd treatment response single mating end 1st contact grouping **Criticality Code Justification:** Feat **Terminal Type:** Tab, solder lug single mating end 1st contact grouping

Contact Material Specification:

Qq-b-750 federal specification single material response single mating end 1st contact grouping

Included Contact Quantity:

6 single mating end 1st contact grouping

Included Contact Type:

Round socket single mating end 1st contact grouping

Special Features:

Polarizing pin in position 4

NSN 5935-01-275-8220

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.006 gold grains, troy
Precious Material:
Gold
Specification Data:
73030-791723 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.