

View Online at <https://aerobasegroup.com/nsn/5935-01-275-8232>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Rectangular shape

**Overall Length:**

2.750 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.375 inches

**Overall Height:**

0.929 inches

**Overall Width:**

1.531 inches

**Environmental Protection:**

Corrosion resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.144 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.875 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Polarization Method:**

Guide pin/socket

**Connector Locking Method:**

Jackscrew

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Insert Material:**

Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic polyester single mating end

**Insert Material Specification:**

Mil-m-14, ty sdg-f or ty gdi-30f military specification 1st material response single mating end and mil-m-14, ty sdg-f or ty gdi-30f military specification 2nd material response single mating end or mil-m-24519 military specification 3rd material response single mating end

**Test Data Document:**

81349-mil-c-28731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Specification Data:**

81349-mil-c-28731/17 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.