

View Online at <https://aerobasegroup.com/nsn/5935-01-275-8234>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling w/strain relief

Overall Length:

3.060 inches

Overall Diameter:

Between 2.056 inches and 2.078 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant

Cable Entrance Diameter:

0.750 inches

Distance From Mounting Shoulder To Front Face:

0.879 inches

Mounting Facility Thickness:

0.250 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

22-55 single mating end

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

226.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp

Thready Qty Per Inch (tpi):

18

Thread Size:

1.500 inches

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification all treatment responses

Shell Material Specification:

Qq-a-591 federal specification single material response

Bushing Accommodation Hole Shape:

Round w/flat

Thread Series Designator:

Unef

Specification Data:

10001-2889412 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0