NSN 5935-01-276-0614

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-276-0614

| Body Style: |
|---|
| Right angle type |
| Overall Length: |
| 1.610 inches |
| Overall Width: |
| 0.520 inches |
| Body Height: |
| 0.330 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 1.0 single mating end single contact grouping |
| Polarization Method: |
| Contact to contact polarizing keys |
| Connector Locking Method: |
| Latch |
| Terminal Location: |
| Side single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Glass single mating end and plastic polyester single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal |
| specification 2nd treatment response single mating end single contact grouping |
| Terminal Type: |
| Tab, solder lug single mating end single contact grouping |
| Included Contact Quantity: |
| 26 single mating end single contact grouping |
| Included Contact Type: |
| Flat pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |

Gold

0.026 gold grains, troy **Precious Material:**

NSN 5935-01-276-0614

Electrical Receptacle Connector - Page 2 of 2



| Shelf Life: |
|-------------------|
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |
| Fiig: |

Mil-std (military Standard):

Mil-g-45204 spec.