# NSN 5935-01-276-1142

Steel

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-276-1142

Body Style:
Straight shape
Overall Length:
2.635 inches
Overall Height:
0.613 inches
Overall Width:
0.605 inches
Unthreaded Mounting Hole Diameter:
0.086 inches
Distance Between Mounting Facility Centers:
2.406 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
50 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
End Application:
5895-01-205-6148 receiver-exciter
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end and glass fiber single mating end
Contact Surface Treatment Specification:
Mil-g-45204, ty ii, gr c, cl 1 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military
specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Shell Material:

# NSN 5935-01-276-1142

Electrical Receptacle Connector - Page 2 of 2



#### **Shell Surface Treatment:**

Chromate and cadmium

# **Shell Surface Treatment Specification:**

Qq-p-416, ty ii, cl 2 federal specification all treatment responses

# **Shell Material Specification:**

Astm a620 assn standard single material response

# **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification all material responses single mating end

# **Included Contact Quantity:**

50 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.050 gold grains, troy

#### **Precious Material:**

Gold

# Shelf Life:

N/a

# **Unit Of Measure:**

# Demilitarization:

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.