## NSN 5935-01-276-1150

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-276-1150

**Body Style:** 

Straight edge type w/mounting flange

**Overall Height:** 

0.740 inches

Overall Width:

0.370 inches

**Unthreaded Mounting Hole Diameter:** 

0.128 inches

**Distance Between Mounting Facility Centers:** 

4.031 inches

**Board Accommodated Length:** 

3.596 inches single board

**Board Accommodated Width:** 

Between 0.055 inches and 0.070 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Polarization Method:** 

Shell

**End Application:** 

6625-01-251-4775 monitor communication

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic polyester single mating end and glass fiber single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Pin single mating end single contact grouping

**Included Contact Quantity:** 

44 single mating end single contact grouping

**Included Contact Type:** 

Bifurcated spring single mating end single contact grouping

## NSN 5935-01-276-1150

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.044 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.