NSN 5935-01-276-1152

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-276-1152 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 1.180 inches **Overall Height:** 1.090 inches **Overall Width:** 2.275 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.149 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.900 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 52 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Polarization boss **Connector Locking Method:** Post jacksocket Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-01-276-1152

Electrical Receptacle Connector - Page 2 of 2



Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-513 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification all material responses single mating end or mil-p-19833, ty gdi-30f military specification all material responses single mating end

Included Contact Quantity:

52 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.052 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Specification Data:

81349-mil-c-28748/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.