Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-276-2327

#### **Body Style:**

Straight type

**Overall Length:** 

2.425 inches

# **Overall Width:**

0.350 inches

### **Body Height:**

0.320 inches

### **Environmental Protection:**

Shock resistant and vibration resistant and moisture resistant and salt water resistant and heat resistant and cold resistant

### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

## **Connector Locking Method:**

Friction

## **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

## **Insert Material:**

Plastic polyphenylene single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type ii, class 1 military specification 1st treatment response single mating end single contact grouping

## **Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-p-46174, class 40, grade e military specification single material response single mating end

# Precious Material And Location:

Contact surfaces gold

# Precious Material And Weight:

0.096 gold grains, troy

# **Precious Material:**

Gold

# Specification Data:

00752-441185 manufacturers specification control

# Shelf Life:

N/a

Receptacle Dummy Connector - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.