## NSN 5935-01-276-2344

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-276-2344

Body Style:
Straight type
Overall Length:
2.406 inches
Overall Width:
0.335 inches
Body Height:
0.238 inches
Environmental Protection:
Shock resistant and humidity resistant and vibration resistant and thermal shock resistant and corrosion resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Glass single mating end and plastic polyamide single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping and qq-n-290 federal specification 2r
treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Contact Material Specification:
Qq-b-750, 1/2 hard federal specification single material response single mating end single contact grouping
Included Contact Quantity:
48 single mating end single contact grouping

### Included Contact Type:

Square socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.048 gold grains, troy

# NSN 5935-01-276-2344

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.