Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-276-5597

Thread Class:
2a Thread Direction:
Right-hand
Body Style:
Straight shape threaded
Overall Length: 1.600 inches
Overall Diameter:
1.641 inches
Environmental Protection:
Vibration resistant and shock resistant and thermal shock resistant and humidity resistant
Distance From Mounting Shoulder To Front Face:
0.920 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
15-35 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
100.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
End Application:
5895-01-205-6148 receiver-exciter
Thready Qty Per Inch (tpi):
18
Thread Size:
1.125 inches
Terminal Location:
Back single mating end single contact grouping



Contact Ma	
	y single mating end single contact grouping
Contact Su	urface Treatment:
Gold single	mating end single contact grouping
Contact Su	urface Treatment Specification:
Mil-g-45204	4 military specification single treatment response single mating end single contact grouping
Terminal T	уре:
Pin single r	nating end single contact grouping
Shell Mate	rial:
Aluminum a	alloy
Shell Surfa	ace Treatment:
Cadmium	
Included C	contact Quantity:
37 single m	nating end single contact grouping
Bushing A	ccommodation Hole Shape:
Round w/fla	at
Included C	Contact Type:
Round pin	single mating end single contact grouping
Precious M	Naterial And Location:
Contact sui	faces gold
Precious M	laterial And Weight:
0.037 gold	grains, troy
Precious N	faterial:
Gold	
Thread Se	ries Designator:
Unef	
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitariz	ation:
No	
Fiig:	
A039b0	
Mil-std (mi	litary Standard):
Mil-g-45204	4 spec.