NSN 5935-01-277-2296

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-277-2296

Body Style:

Straight shape

Overall Length:

4.256 inches

Overall Diameter:

Between 1.860 inches and 1.902 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant

Mating End Quantity:

2

Contact Position Arrangement Style:

25-61 2nd mating end

Contact Removability:

Removable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 1st mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

222.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin and bayonet latch

End Application:

4910-01-142-2640 m1 peculiar hardware

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold 2nd mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, gr c, cl 1 military specification 1st treatment response 1st mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response 1st mating end single contact grouping

Shell Material:

Aluminum alloy and aluminum alloy 6061 or aluminum alloy and aluminum alloy 380.0 or aluminum alloy and aluminum alloy a380.0

Shell Surface Treatment:

Nickel and cadmium

Shell Surface Treatment Specification:

Mil-c-26074, cl 3 or 4, gr b military specification 1st treatment response and qq-p-416 federal specification 2nd treatment response

Shell Material Specification:

Qq-a-367, t6 federal specification 2nd material response or qq-a-591 federal specification 4th material response or qq-a-591 federal specification all material responses

Included Contact Quantity:

61 2nd mating end single contact grouping

NSN 5935-01-277-2296

Connector Adapter - Page 2 of 2



Included Contact Type:
Round socket 1st mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.093 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard): Mil-g-45204 spec.

A039b0