## NSN 5935-01-277-3019

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-277-3019 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.156 inches **Overall Height:** 1.375 inches **Overall Width:** 1.375 inches **Environmental Protection:** Weatherproof and heat resistant and cold resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches **Distance From Mounting Shoulder To Front Face:** 0.562 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 15000.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18

Thread Size:

1.125 inches

## NSN 5935-01-277-3019

Electrical Receptacle Connector - Page 2 of 2



## **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber synthetic single mating end **Contact Surface Treatment Specification:** Mil-g-45204, class i military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Shell Surface Treatment Specification:** Qq-p-416, type ii federal specification all treatment responses **Shell Material Specification:** Qq-a-591 federal specification single material response **Insert Material Specification:** Zz-r-765 federal specification single material response single mating end **Included Contact Quantity:** 4 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Mil-g-45204 spec.

Mil-std (military Standard):

Fiig: A039b0