

View Online at <https://aerobasegroup.com/nsn/5935-01-277-5209>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

1.850 inches

Overall Height:

0.712 inches

Overall Width:

0.250 inches

Environmental Protection:

Vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

300.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type gdi-30f or type sdg-f military specification single material response single mating end

Included Contact Quantity:

30 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.