

View Online at <https://aerobasegroup.com/nsn/5935-01-277-5229>

Body Style:

Straight edge type w/card guide

Overall Length:

4.652 inches

Overall Width:

0.438 inches

Body Height:

0.406 inches

Board Accommodated Length:

4.532 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1800.0 single mating end single contact grouping

Polarization Method:

Inter-contact polarizing keys

Connector Locking Method:

Friction

End Application:

6625-01-212-3679 generator, sweep

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic phenolic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Included Contact Quantity:

56 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.056 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.