Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-277-7945

Thread Class:
2a
Body Style:
Straight shape, external coupling
Overall Length:
0.885 inches
Overall Height:
1.688 inches
Overall Width:
1.688 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.375 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.375 inches
Distance From Mounting Shoulder To Front Face:
0.322 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
24-61 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
126.0
Shell Type:
Solid
Thready Qty Per Inch (tpi):
18
Thread Size:
1.438 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Conner allow single mating and single contact growning

Copper alloy single mating end single contact grouping



Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Glass fiber single mating end Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel and cadmium

Included Contact Quantity:

61 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0