# NSN 5935-01-277-8559

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-277-8559

Body Style:
Straight type
Overall Length:
2.050 inches
Overall Height:
0.465 inches
Overall Width:
0.250 inches
Environmental Protection:
Cold resistant and heat resistant and vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock
resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
1.800 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
500.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Conner alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end and glass fiber single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Solder well single mating end single contact grouping

## **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

# NSN 5935-01-277-8559

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

Mil-m-14g, ty gdi-30f or ty sdg-f military specification all material responses single mating end

**Unable To Decode:** 

Unable to decode and unable to decode

**Included Contact Quantity:** 

24 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.024 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.