NSN 5935-01-278-3117

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-278-3117

Thread Class: 2a and 2a and 2a **Thread Direction:** Left-hand and right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.907 inches **Overall Diameter:** 3.125 inches **Environmental Protection:** Corrosion resistant and explosion proof and moisture resistant and weatherproof **Distance From Mounting Shoulder To Front Face:** 1.172 inches **Mounting Facility Thickness:** Between 0.094 inches and 0.203 inches **Threaded Device Type:** Back shell and coupling facility and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 40-67 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 22.0 single mating end 1st contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 16 and 10 and 16

Thread Size:

2.312 inches and 2.500 inches and 2.625 inches

NSN 5935-01-278-3117

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Silver single mating end all contact groupings
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum
Shell Surface Treatment:
Anodize
Included Contact Quantity:
10 single mating end 2nd contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.011 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns and double stub and un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0