NSN 5935-01-278-3427

Terminal Location:

Back single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-278-3427 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.880 inches **Overall Height:** Between 1.146 inches and 1.170 inches **Overall Width:** Between 4.300 inches and 4.330 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and corrosion resistant and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.558 inches and 0.566 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 3.870 inches and 3.880 inches **Distance From Mounting Shoulder To Front Face:** Between 0.615 inches and 0.630 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 64 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Mating end and guide pin/socket Shell Type: **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -65.0 degrees celsius and 200.0 degrees celsius Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches

NSN 5935-01-278-3427

Electrical Receptacle Connector - Page 2 of 3



_							
r -	n	+-	rt.	N/I	atα	ria	
·	OI.	ιa	·ι	IVI	alc	ııа	ı .

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, grade a, cl 3 or 4 military specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

64 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Furnished items - spare contact

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.064 gold grains, troy

Precious Material:

Gold

Supplementary Features:

Mounting method - spring

Test Data Document:

81349-mil-c-83733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-83733/7 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

NSN 5935-01-278-3427

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.