NSN 5935-01-278-7066

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-278-7066

Body Style:

Right angle type

Overall Length:

Between 5.745 inches and 5.755 inches

Overall Height:

Between 0.560 inches and 0.600 inches

Overall Width:

Between 0.819 inches and 0.829 inches

Unthreaded Mounting Hole Diameter:

0.100 inches

Distance Between Mounting Facility Centers:

Between 5.445 inches and 5.455 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

2.25 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping and tin single mating end single contact grouping

Insert Material:

Glass fiber single mating end and plastic polyphenylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape pin left-hand at 6 oclock and d shape pin right-hand at 6 oclock

Insert Material Specification:

Mil-p-46174 military specification all material responses single mating end

NSN 5935-01-278-7066

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 196 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.196 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Mil-std (military Standard): Mil-g-45204 spec.

Fiig: A039b0