

View Online at <https://aerobasegroup.com/nsn/5935-01-278-9973>

Body Style:

Angle shape, w/ or w/o cover

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

B4s single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

100.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

22.5

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Insert Material:

Plastic polyester single mating end and glass fiber single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0