Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-278-9973

#### Body Style:

Angle shape, w/ or w/o cover

#### Threaded Device Type:

Coupling facility

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

B4s single mating end

### Contact Removability:

Removable single mating end single contact grouping

## Contact Maximum Current Rating In Amps:

100.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

## Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end single contact grouping

### **Polarization Method:**

Key, multiple key groove

### Insert Position In Deg:

22.5

#### Shell Type:

Solid

### **Connector Locking Method:**

Externally threaded shell

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### Insert Material:

Plastic polyester single mating end and glass fiber single mating end

### **Terminal Type:**

Crimp single mating end single contact grouping

### Shell Material:

Aluminum

# Included Contact Quantity:

4 single mating end single contact grouping

# Included Contact Type:

Round pin single mating end single contact grouping

### Shelf Life:

N/a

### Unit Of Measure:

---



Demilitarization:

No

Fiig:

A039b0