

View Online at <https://aerobasegroup.com/nsn/5935-01-279-1058>

**Body Style:**

Straight shape

**Overall Length:**

1.480 inches

**Overall Height:**

0.410 inches

**Overall Width:**

0.630 inches

**Environmental Protection:**

Cold resistant and heat resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Connector Locking Method:**

Friction

**Connector Cable Strain Relief Method:**

Crimp type

**Cable Opening Length:**

1.480 inches

**Cable Opening Width:**

0.630 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Glass single mating end and plastic polyester single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, ty ii, gr c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

**Included Contact Quantity:**

26 single mating end single contact grouping

**Included Contact Type:**

Flat socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.026 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.