Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-279-3704

# Body Style:Straight shape, external couplingOverall Length:34.1 millimetersOverall Height:Between 42.3 millimeters and 43.4 millimetersOverall Width:Between 42.3 millimeters and 43.4 millimetersUnthreaded Mounting Hole Diameter:Between 3.1 millimeters and 3.5 millimetersCenter To Center Distance Between Mounting Facilities Parallel To Height:34.9 millimetersJistance Between Centerlines Of Mounting Facilities Parallel To Body Width:34.9 millimeters

Distance From Mounting Shoulder To Front Face:

Between 19.2 millimeters and 20.8 millimeters

#### Mating End Quantity:

1

**Contact Position Arrangement Style:** 

23-55 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### Insert Position In Deg:

80.0 and 280.0

#### Shell Type:

Solid

#### Connector Locking Method:

Detent

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### Shell Material:

Aluminum alloy

# NSN 5935-01-279-3704

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

# Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

# Included Contact Quantity:

55 single mating end single contact grouping

# Included Contact Type:

Round pin single mating end single contact grouping

# Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.055 gold grains, troy

Precious Material:

Gold

# Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### Specification Data:

81349-dod-c-38999/42 government specification

Shelf Life: N/a

Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.