

NSN 5935-01-279-5178 Electrical Receptacle Connector Body - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-279-5178 **Thread Class:** 2a and 2b and 2a **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Rectangular shape **Overall Length:** 2.846 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 2.276 inches and 2.286 inches

**Overall Height:** 

Between 0.851 inches and 0.861 inches

**Overall Width:** 

1.005 inches

#### **Environmental Protection:**

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.148 inches and 0.155 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.463 inches and 0.473 inches

# **Threaded Device Type:**

Coupling facility and mounting stud

**Mating End Quantity:** 

## **Contact Position Arrangement Style:**

50 single mating end

## **Polarization Method:**

Jackscrew and shell

Shell Type:

Solid

## **Connector Locking Method:**

Jackscrew-socket

# **Thread Length:**

0.320 inches

## Thready Qty Per Inch (tpi):

32 and 32 and 40

#### **Thread Size:**

0.138 inches and 0.138 inches and 0.112 inches

## **Insert Material:**

Plastic diallyl phthalate single mating end and glass fiber single mating end

## **Criticality Code Justification:**

Feat

# NSN 5935-01-279-5178

Electrical Receptacle Connector Body - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, class 1 or class 2 federal specification all treatment responses
Insert Material Specification:
Mil-m-14, ty sdg-f military specification all material responses single mating end or mil-p-19833, ty gdi-30f military specification all material
responses single mating end
Shell Guide Type And Location Designator:
A pin
Special Features:
Item must comply with requirements of desc production standard no. L03996; for navy nuclear propulsion plant products only
Thread Series Designator:
Unc and unc and unc
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.