

View Online at <https://aerobasegroup.com/nsn/5935-01-279-5222>

Body Style:

Straight edge type w/mounting flange

Overall Length:

Between 6.940 inches and 6.970 inches

Overall Height:

0.860 inches

Overall Width:

Between 0.485 inches and 0.490 inches

Unthreaded Mounting Hole Diameter:

Between 0.157 inches and 0.163 inches

Distance Between Mounting Facility Centers:

Between 6.651 inches and 6.661 inches

Board Accommodated Length:

6.195 inches single board and 6.205 inches single board

Board Accommodated Width:

0.136 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sgd-f military specification single material response single mating end

Included Contact Quantity:

122 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.122 gold grains, troy

Precious Material:

Gold

Specification Data:

04614-5935-088 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.