

View Online at <https://aerobasegroup.com/nsn/5935-01-279-5222>

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

Between 6.940 inches and 6.970 inches

**Overall Height:**

0.860 inches

**Overall Width:**

Between 0.485 inches and 0.490 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.157 inches and 0.163 inches

**Distance Between Mounting Facility Centers:**

Between 6.651 inches and 6.661 inches

**Board Accommodated Length:**

6.195 inches single board and 6.205 inches single board

**Board Accommodated Width:**

0.136 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, ty sgd-f military specification single material response single mating end

**Included Contact Quantity:**

122 single mating end single contact grouping

**Included Contact Type:**

Bifurcated spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.122 gold grains, troy

**Precious Material:**

Gold

**Specification Data:**

04614-5935-088 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.