NSN 5935-01-279-8011

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-279-8011

Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Rectangular shape
Overall Length:
2.986 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.375 inches
Overall Height:
0.890 inches
Overall Width:
1.768 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.150 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.875 inches
Threaded Davies Type:
Threaded Device Type:
Coupling facility and mounting stud
Coupling facility and mounting stud
Coupling facility and mounting stud Mating End Quantity:
Coupling facility and mounting stud Mating End Quantity: 1
Coupling facility and mounting stud Mating End Quantity: 1 Contact Position Arrangement Style:
Coupling facility and mounting stud Mating End Quantity: 1 Contact Position Arrangement Style: 25-104 single mating end
Coupling facility and mounting stud Mating End Quantity: 1 Contact Position Arrangement Style: 25-104 single mating end Contact Removability:
Coupling facility and mounting stud Mating End Quantity: 1 Contact Position Arrangement Style: 25-104 single mating end Contact Removability: Nonremovable single mating end single contact grouping
Coupling facility and mounting stud Mating End Quantity: 1 Contact Position Arrangement Style: 25-104 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps:
Coupling facility and mounting stud Mating End Quantity: 1 Contact Position Arrangement Style: 25-104 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping
Coupling facility and mounting stud Mating End Quantity: 1 Contact Position Arrangement Style: 25-104 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method:
Coupling facility and mounting stud Mating End Quantity: 1 Contact Position Arrangement Style: 25-104 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Shell
Coupling facility and mounting stud Mating End Quantity: 1 Contact Position Arrangement Style: 25-104 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Shell Shell Type:
Coupling facility and mounting stud Mating End Quantity: 1 Contact Position Arrangement Style: 25-104 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Shell Shell Type: Solid
Coupling facility and mounting stud Mating End Quantity: 1 Contact Position Arrangement Style: 25-104 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Shell Shell Type: Solid Connector Locking Method:
Coupling facility and mounting stud Mating End Quantity: 1 Contact Position Arrangement Style: 25-104 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Shell Shell Type: Solid Connector Locking Method: Jackscrew-socket
Coupling facility and mounting stud Mating End Quantity: 1 Contact Position Arrangement Style: 25-104 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Shell Shell Type: Solid Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi):

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-279-8011

Electrical Receptacle Connector - Page 2 of 2

