Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-279-8621

Thread Class:

2a and 2g

Thread Direction:

Left-hand and right-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

2.937 inches

Overall Height:

2.250 inches

Overall Width:

2.250 inches

Environmental Protection:

Cold resistant and heat resistant and humidity resistant and moisture resistant and corrosion resistant and salt water resistant and dust

resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.203 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.688 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.688 inches

Distance From Mounting Shoulder To Front Face:

1.609 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

28-840 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

60.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

18 and 8

NSN 5935-01-279-8621

Electrical Receptacle Connector - Page 2 of 2



	hread Size: 613 inches and 2.000 inches
	erminal Location:
	ack single mating end single contact grouping
	ontact Material:
	opper alloy single mating end single contact grouping
	ontact Surface Treatment:
	ilver single mating end single contact grouping
	sert Material:
	ubber synthetic single mating end and plastic single mating end
	ontact Surface Treatment Specification:
	q-s-365 federal specification single treatment response single mating end single contact groupin
	erminal Type:
	rimp single mating end single contact grouping
-	hell Material:
-	hell Surface Treatment:
	nodize
	cluded Contact Quantity:
	single mating end single contact grouping
	cluded Contact Type:
	ound pin single mating end single contact grouping
	recious Material And Location:
-	ontact surfaces silver
	recious Material And Weight:
	020 silver grains, troy
	recious Material:
-	
	hread Series Designator:
	pt and special acme
	helf Life:
	/a
U	nit Of Measure:
	emilitarization:
Ν	
Fi	iig: