

View Online at <https://aerobasegroup.com/nsn/5935-01-281-0042>

Body Style:

Straight shape, external coupling

Overall Length:

36.5 millimeters

Overall Height:

Between 29.3 millimeters and 30.3 millimeters

Overall Width:

Between 29.3 millimeters and 30.3 millimeters

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

Between 3.1 millimeters and 3.2 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 22.9 millimeters and 23.1 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 22.9 millimeters and 23.1 millimeters

Distance From Mounting Shoulder To Front Face:

Between 18.2 millimeters and 18.6 millimeters

Mating End Quantity:

1

Contact Position Arrangement Style:

"14s-6, 11-6" single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

End Application:

2320-01-123-1612 light armored vehicle

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping or gold single mating end single contact grouping or rhodium single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Chromate and cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses

Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver or contact surfaces gold or contact surfaces rhodium

Precious Material And Weight:

0.030 silver grains, troy or 0.030 gold grains, troy or 0.030 rhodium grains, troy

Precious Material:

Silver or gold or rhodium

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0