NSN 5935-01-281-1566

Electrical Receptacle Connector - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5955-01-261-1566 |
|--|
| Body Style: |
| Right angle type |
| Overall Length: |
| 2.730 inches |
| Overall Width: |
| 0.360 inches |
| Body Height: |
| 0.245 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 3.0 single mating end single contact grouping |
| Connector Locking Method: |
| Friction |
| End Application: |
| 6625-01-231-4890 test set, communication |
| Terminal Location: |
| Side single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic polyester single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Tab, solder lug single mating end single contact grouping |
| Included Contact Quantity: |
| 52 single mating end single contact grouping |
| Included Contact Type: |
| Flat pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.052 gold grains, troy |
| Precious Material: |

Gold

NSN 5935-01-281-1566

Electrical Receptacle Connector - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| | |
| Fiig: | |

Mil-std (military Standard):

Mil-g-45204 spec.

Shelf Life: