## NSN 5935-01-281-2725

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-281-2725 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.215 inches **Overall Height:** 1.188 inches **Overall Width:** 1.188 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** 0.562 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 14s-7 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 180.0 Shell Type: Solid Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.875 inches **Terminal Location:** 

**Contact Material:** 

Copper alloy single mating end single contact grouping

Back single mating end single contact grouping

## NSN 5935-01-281-2725

Electrical Receptacle Connector - Page 2 of 2



| $^{\circ}$ | ntact | Surfa | CO Tr  | -patm | ont. |
|------------|-------|-------|--------|-------|------|
| Ju         | IIIau | Julia | 166 II | Cauii | en.  |

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium and chromate

**Included Contact Quantity:** 

3 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material:** 

Gold and silver

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0