NSN 5935-01-281-5011

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-281-5011

Body Style:

Straight shape, flush mount

Overall Length:

1.326 inches

Overall Height:

Between 4.300 inches and 4.330 inches

Overall Width:

Between 1.985 inches and 2.015 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

4.026 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Distance From Mounting Shoulder To Front Face:

Between 0.055 inches and 0.065 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd 3rd mating end

Contact Removability:

Removable 2nd mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back 1st mating end single contact grouping

Contact Material:

Copper alloy 2nd mating end single contact grouping

Contact Surface Treatment:

Gold 2nd mating end single contact grouping

Insert Material:

Plastic diallyl phthalate all mating ends and glass fiber all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response 1st mating end single contact grouping

Terminal Type:

Crimp 1st mating end single contact grouping

Shell Material:

Aluminum alloy

NSN 5935-01-281-5011

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2 federal specification all treatment responses

Shell Material Specification:

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

Insert Material Specification:

Mil-m-14, ty gdi-30f, sdg-f military specification 1st material response all mating ends and mil-m-14, ty gdi-30f, sdg-f military specification 2nd material response all mating ends or allied chemical 1288 bx mfr ref 3rd material response all mating ends and mil-m-14 military specification 4th material response all mating ends

Included Contact Quantity:

106 1st mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.212 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.