

View Online at <https://aerobasegroup.com/nsn/5935-01-281-6974>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight type

Overall Length:

Between 2.340 inches and 2.360 inches

Overall Height:

Between 0.640 inches and 0.690 inches

Overall Width:

Between 0.245 inches and 0.255 inches

Environmental Protection:

Humidity resistant and corrosion resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Distance Between Mounting Facility Centers:

Between 2.095 inches and 2.105 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end 1st contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping

Insert Material:

Glass fiber single mating end and plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, gr c military specification 1st treatment response single mating end 1st contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end 1st contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Solder well single mating end 1st contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end 1st contact grouping

Insert Material Specification:

Mil-m-24519, ty gpt-30f military specification all material responses single mating end or mil-p-46174, cl 40, gr e military specification all material responses single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

29 single mating end 1st contact grouping

Included Contact Type:

Round socket single mating end 1st contact grouping

Special Features:

Contact position number 15 is missing

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.029 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Specification Data:

90536-7915667 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.